

## 14 x 40 Precision Metal Lathe



SPECIFICATIONS	14 x 40	
CAPACITIES		
Swing over bed	14"	
Swing over cross slide	8 1/4"	
Swing in gap	20"	
Length of gap	9 1/4"	
HEADSTOCK		
Spindle bore	1 1/2"	
Spindle speeds - number	12	
Spindle speeds - range	40 - 1800 RPM	
Spindle nose	D1 - 4	
FEEDS & THREADS		
Threads per inch - number/range	40 / 4 - 112 TPI	
Metric threads - number/range	24 / .45 - 7.5	
Longitudinal feeds - number/range	40 / .00110271 IPR	
Cross feeds - number/range	40 / .0003 - 0090 IPR	
Leadscrew - diamter/range	7/8" 8 TPI	
CARRIAGE & APRON		
Cross slide travel	6 1/2"	
Compound travel	3 1/4"	
TAPER ATTACHMENT		
Degrees of taper	+/- 8 degrees	
Length of taper per setting	13"	
BED		
Width of bed	10 1/4"	
Bed way hardness (Rockwell C)	42 - 48	
TAILSTOCK		
Travel of spindle barrel	5"	
Diameter of spindle barrel	1 3/4"	
Taper of center	#3 MT	
MOTORS		
Spindle motor	4 HP	
Coolant pump	1/8 HP	
SHIPPING DATA		
Length x Width x Height	78" x 36" x 54"	
Weight	2,491 lbs.	



## **INCLUDED ACCESSORIES**

- 8" 3 jaw chuck (D1-4)
- 8" 4 jaw chuck (D1-4)
- Steady rest
- Follow rest
- Full length splash guard
- Halogen work light
- Taper attachment
- Coolant system
- Thread dial
- · Micrometer carriage stop

## **STANDARD FEATURES**

- · Inch and metric threading
- Hardened & precision ground bed ways
- Removable gap
- T-slotted compound
- All cast iron construction
- Foot brake
- Dual dials inch/metric
- Dual voltage 220/440 volt / 3 phase / 60 Hz

1-800-654-3262



WARRANTY: A copy of Summit Machine Tool Manufacturing L.L.C.'s standard written warranty is attached to each Summit Machine. Call or write to Summit for a copy or for further information concerning Summit's standard warranty. All purchases are subject to Summit's standard written warranty. Specifications are subject to change without notice.

POINT OF OPERATION guarding is the responsibility of the end user. For information contact your local OSHA office.

## **Summit Machine Tool Manufacturing L.L.C.**

P.O. Box 1402 • Oklahoma City, OK 73101 • 405.235.2075 • FAX 405.232.5169
A Subsidiary of LSB Industries, Inc.
www.summitmachinetool.com